



Can Freezer

Scancool - FT 87 BE



Dimensions and weight

Product dimensions, HxWxD, mm	836 x 565 x 565
Packaging dimensions, HxWxD, mm	890 x 580 x 580
Gross volume, L	85
Net volume, L	85
Gross- / Net volume, L	85 / 85
Internal dimensions, HxWxD, mm	493 x 470 x 470
Gross- / Net weight, kg	31 / 28

Performance and consumption

Energy efficiency class	D
Daily Energy Consumption, kWh/24	2,801
Annual energy cons. kWh/a	1095
Energy Efficiency Index (EEI)	46,6
Refrigeration / freezing technique	Static
Climate class	4
Temperature class	L1
Type of refrigerant / gas gr.	R600a / 50
Bulb Watt, W	N/A
NoFrost	No
Energy efficiency class	D

Installation and power

Voltage / hertz, V/hz	220-240V / 50hz
No. of electrical phases	1L+N
Watt / Ampere, W/A	145 / 0.95
Length of Powercord, cm	220

Design and comfort

Controller	Mechanical
Control panel	None
Digital display	No
Canopy light sign	No
Internal light	No light
External thermometer	No
Door- / lid type	Right hinged
Handle	Integrated
Number of castors, pcs	4 castors
Lock & Key	No

Colour and material

Outside colour	Black
Inside Colour	White
Colour and material of door/lid	Flip glas lid

Features

Number of baskets, pcs	1 basket
Adjustable shelves	No

Item number	26320087BE10000	Taric goods code	8418501190
EAN code	5704704015593	QTY in 40HQ	240

Short Description

The FT 87 BE is black, but can also be decorated as desired. The round shape makes the cooler suitable for decorations. It is eye-catching and does not take up much space on the floor. The barrel shape makes it easy to place in any room, both indoors and outdoors.

Holds 85 liters and has a two-piece glass tilting lid, which makes it easy to see the contents and makes it easy to get to the ice. The freezer is fitted with 4 wheels, making it easy to move around, even when it is filled with ice.

It comes with 1 removable wire basket which is handy and makes it easy for you to arrange your products in the freezer.

Key features

- Split flip glass lid
- Suitable for branding
- 1 wire basket
- 4 strong castors
- Temperature range <-18°C

Measurement drawing

